




Tapping saddle Monobloc version

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integrated cutter to tap live mains under pressure
- Complete with moulded-on lower part
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap
- *Compatible with GASSTOP type GS



	d	d1	Code	SP	GP	Weight	d2	H	H1	L	L1	z
	(mm)	(mm)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
*	63	20	193 131 932	1	20	0.368	25	146	44	144	76	110
	63	25	193 131 933	1	20	0.393	25	146	44	144	76	110
*	63	32	193 131 934	1	20	0.376	25	146	44	144	76	110
*	90	20	193 131 952	1	12	0.494	32	198	61	162	76	115
	90	25	193 131 953	1	12	0.503	32	198	61	162	76	115
*	90	32	193 131 954	1	12	0.505	32	198	61	162	76	115
	90	63	193 131 957	1	10	0.667	32	198	61	162	76	115
*	110	20	193 131 962	1	9	0.560	32	208	71	162	76	115
	110	25	193 131 963	1	9	0.570	32	208	71	162	76	115
*	110	32	193 131 964	1	9	0.574	32	208	71	162	76	125
	110	63	193 131 967	1	8	0.684	32	208	71	162	100	160
*	125	20	193 131 972	1	6	0.562	32	216	79	162	76	120
	125	25	193 131 973	1	6	0.552	32	216	79	162	76	120
*	125	32	193 131 974	1	6	0.574	32	216	79	162	76	120
	125	63	193 131 977	1	6	0.704	32	216	79	162	76	120
*	160	20	193 131 992	1	6	0.631	32	233	96	162	76	120
	160	25	193 131 993	1	6	0.641	32	233	96	162	76	125
*	160	32	193 131 994	1	6	0.648	32	233	96	162	76	130
	160	63	193 131 997	1	6	0.794	32	233	96	162	100	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>