



Fitinguri de tranzitie PE/otel

- **PE 100 SDR 11** (ISO S5)
- 10 bar Gaz / 16 bar Apa
- Pot fi sudate prin electrofuziune
- PE coated for corrosion resistance
- * Steel pipe galvanized

	d	d1	Cod	SP	Greutate	L	L1	L2
	(mm)	(inch)			(kg)	(mm)	(mm)	(mm)
*	20	½	775 641 502	1	0,450	425	15	80
	25	¾	775 641 507	21	0,658	463	35	90
	32	1	775 641 510	18	0,988	460	35	96
	40	1 ¼	775 641 514	12	1,208	470	35	100
	50	1 ½	775 641 518	8	1,355	480	35	110
	63	2	775 641 524	6	2,011	480	35	110
	75	2 ½	775 641 632	2	2,983	540	35	127
	90	3	775 641 636	2	3,762	580	45	141
	110	3	775 641 640	2	4,381	580	45	145
	110	4	775 641 641	2	6,633	585	45	145
	125	4	775 641 645	2	6,833	585	45	148
	160	6	775 641 655	1	12,406	610	45	158
	180	6	775 641 659	1	11,935	610	45	168
	200	8	775 642 664	1	19,647	630	45	155
	225	8	775 642 669	1	20,154	607	45	145
	250	8	775 642 665	1	21,354	630	45	200
	250	10	775 642 666	8	30,000	640	45	140
	280	10	775 642 673	8	31,000	640	45	160
	315	12	775 642 672	6	35,000	725	45	220
	355	12	775 642 675	6	49,000	735	45	260
	400	16	775 642 678	4	94,000	770	45	190

Datele tehnice nu sunt obligatorii. Acestea nu constituie garantia caracteristicilor, a proprietatilor sau a durabilitatii. Acestea sunt supuse modificarii. Se aplica Condiitiile noastre Generale de Vanzare.

Georg Fischer Rohrleitungssysteme (Elvetia) SA Sucursala Bucuresti, Tel. +40 31 104 0492, Internet: www.georgfischer.com.ro